


## 6000 Series



Tipo	Atore el taladro	Exterior	Ancho	Ancho	Radio	Capacidad de carga (N)		Max velocidad	
	D (mm)	D(mm)	B milímetro	B1 milímetro	Rs (min) (milímetros)	Dinámico	Estática	Grasa	Aceite
						Cr	Corazón	*1000RPM	*1000RPM
6010	50	80	16	16	1.50	18510	13260	8.40	9.90
6009	45	75	16	16	1.50	15150	9660	9.20	11
6008	40	68	15	15	1.10	14250	9220	10	12
6007	35	62	14	14	1.10	13560	8250	11	13
6006	30	55	13	13	1.10	11240	6610	13	15
6005	25	47	12	12	1	8550	4690	15	18
6004	20	42	12	12	0.60	7960	4050	17	21
6002	15	32	9	9	0.30	4750	2270	23	27
6003	17	35	10	10	0.30	5090	2630	21	25
6001	12	28	8	8	0.30	4340	1910	27	32
6000	10	26	8	8	0.30	3860	1570	31	36
609	9	24	7	7	0.30	3356	1444	32	38
608	8	22	7	7	0.30	3293	1379	34	40
607	7	19	6	6	0.30	2336	896	36	43
606	6	17	6	6	0.30	2263	846	38	45
605	5	14	5	5	0.20	1329	507	40	50